

SP

Super Precision Keyless Drill Chuck



MODEL	CAPACITY		MOUNT	SIZES mm.			WEIGHT
no.	mm.	inches	K	Ø	L1	L2	gr.
SP-1.5 J-0/B-6	0,2 - 1,5	0,008" - 1/16"	J-0/B-6	19,4	35	37,3	80
SP-03 J-0/B-6	0,3 - 3	1/64" - 1/8"	J-0/B-6	24,5	44	47,5	200
SP-03 B-10	0,3 - 3	1/64" - 1/8"	B-10	24,5	44	47,5	200
SP-03 J-1	0,3 - 3	1/64" - 1/8"	J-1	24,5	44	47,5	200
SP-03 R-5/16	0,3 - 3	1/64" - 1/8"	5/16" x 24	24,5	44	47,5	200
SP-06 B-10	0,3 - 6,5	1/64" - 1/4"	B-10	33	62	70	360
SP-06 B-12	0,3 - 6,5	1/64" - 1/4"	B-12	33	62	70	360
SP-06 J-1	0,3 - 6,5	1/64" - 1/4"	J-1	33	62	70	360
SP-08 B-12	0,3 - 8	1/64" - 5/16"	B-12	38	67	74	460
SP-08 J-1	0,3 - 8	1/64" - 5/16"	J-1	38	67	74	460
SP-08 J2S	0,3 - 8	1/64" - 5/16"	J2S	38	67	74	460
SP-08 R-3/8	0,3 - 8	1/64" - 5/16"	3/8" x 24	38	67	74	460
SP-10 B-12	0,5 - 10	1/32" - 3/8"	B-12	43	81	89	720
SP-10 B-16	0,5 - 10	1/32" - 3/8"	B-16	43	81	89	720
SP-10 J-2	0,5 - 10	1/32" - 3/8"	J-2	43	81	89	720
SP-10 J-33	0,5 - 10	1/32" - 3/8"	J-33	43	81	89	720
SP-10 R-3/8	0,5 - 10	1/32" - 3/8"	3/8" x 24	43	81	89	720
SP-10 R-1/2	0,5 - 10	1/32" - 3/8"	1/2" x 20	43	81	89	720
SP-13 B-16	1 - 13	1/32" - 1/2"	B-16	49	91	103	1.000
SP-13 J-2	1 - 13	1/32" - 1/2"	J-2	49	91	103	1.000
SP-13 J-33	1 - 13	1/32" - 1/2"	J-33	49	91	103	1.000
SP-13 J-6	1 - 13	1/32" - 1/2"	J-6	49	91	103	1.000
SP-13 R-1/2	1 - 13	1/32" - 1/2"	1/2" x 20	49	91	103	1.000
SP-16 B-16	3 - 16	1/8" - 5/8"	B-16	55	95	107	1.320
SP-16 B-18	3 - 16	1/8" - 5/8"	B-18	55	95	107	1.320
SP-16 J-33	3 - 16	1/8" - 5/8"	J-33	55	95	107	1.320
SP-16 J-6	3 - 16	1/8" - 5/8"	J-6	55	95	107	1.320