

HEXA

Portabrocas integral de precisión con Llave Hexagonal

REFERENCIA	CAPACIDAD		FIJACIÓN	REFRIG.	DIMENSIONES			ROSCA	PESO
número	mm	pulgadas	ISO	interior	Ø	L1	L2	tirante	kg
HX-13 ID-40	1 - 13	1/32" - 1/2"	40	-	54	91	100	M16	1,92
HX-13 ID-40/R	1 - 13	1/32" - 1/2"	40	B+AD	54	91	100	M16	1,92
HX-13 ID-50	1 - 13	1/32" - 1/2"	50	-	54	93	102	M24	3,46
HX-13 ID-50/R	1 - 13	1/32" - 1/2"	50	B+AD	54	93	102	M24	3,46
HX-16 ID-40	3 - 16	1/8" - 5/8"	40	-	57	94	101	M16	2,10
HX-16 ID-40/R	3 - 16	1/8" - 5/8"	40	B+AD	57	94	101	M16	2,10
HX-16 ID-50	3 - 16	1/8" - 5/8"	50	-	57	96	103	M24	3,56
HX-16 ID-50/R	3 - 16	1/8" - 5/8"	50	B+AD	57	96	103	M24	3,56
HX-13 BT-40	1 - 13	1/32" - 1/2"	40	-	54	96	105	M16	2,04
HX-13 BT-40/R	1 - 13	1/32" - 1/2"	40	B+AD	54	96	105	M16	2,04
HX-13 BT-50	1 - 13	1/32" - 1/2"	50	-	54	107	116	M24	4,38
HX-13 BT-50/R	1 - 13	1/32" - 1/2"	50	B+AD	54	107	116	M24	4,38
HX-16 BT-40	3 - 16	1/8" - 5/8"	40	-	57	99	106	M16	2,22
HX-16 BT-40/R	3 - 16	1/8" - 5/8"	40	B+AD	57	99	106	M16	2,22
HX-16 BT-50	3 - 16	1/8" - 5/8"	50	-	57	110	117	M24	4,48
HX-16 BT-50/R	3 - 16	1/8" - 5/8"	50	B+AD	57	110	117	M24	4,48
HX-13 DIN-40	1 - 13	1/32" - 1/2"	40	-	54	82	91	M16	1,84
HX-13 DIN-50	1 - 13	1/32" - 1/2"	50	-	54	85	94	M24	3,32
HX-16 DIN-40	3 - 16	1/8" - 5/8"	40	-	57	85	92	M16	2,00
HX-16 DIN-50	3 - 16	1/8" - 5/8"	50	-	57	88	95	M24	3,42
HX-13 HSK-50	1 - 13	1/32" - 1/2"	50	-	54	112	121	-	1,38
HX-13 HSK-50/R	1 - 13	1/32" - 1/2"	50	A	54	112	121	-	1,38
HX-13 HSK-63	1 - 13	1/32" - 1/2"	63	-	54	98	107	-	1,78
HX-13 HSK-63/R	1 - 13	1/32" - 1/2"	63	A	54	103	112	-	1,78
HX-13 HSK-100	1 - 13	1/32" - 1/2"	100	-	54	110	119	-	4,38
HX-13 HSK-100/R	1 - 13	1/32" - 1/2"	100	A	54	98	107	-	4,38
HX-16 HSK-50	3 - 16	1/8" - 5/8"	50	-	57	115	122	-	1,88
HX-16 HSK-50/R	3 - 16	1/8" - 5/8"	50	A	57	115	122	-	1,88
HX-16 HSK-63	3 - 16	1/8" - 5/8"	63	-	57	101	108	-	4,48
HX-16 HSK-63/R	3 - 16	1/8" - 5/8"	63	A	57	106	113	-	4,48
HX-16 HSK-100	3 - 16	1/8" - 5/8"	100	-	57	113	120	-	4,48
HX-16 HSK-100/R	3 - 16	1/8" - 5/8"	100	A	57	101	108	-	4,48

DIN-69871-A
A, B, AD




MAS 403-BT [JIS-6339A]
A, B, AD



DIN-2080



DIN-69893-A
[HSK]



HEXA

Portabrocas integral de precisión con Llave Hexagonal

REFERENCIA	CAPACIDAD		FIJACIÓN	REFRIG.	DIMENSIONES			ROSCA	PESO
número	mm	pulgadas	ISO	interior	Ø	L1	L2	tirante	kg
HX-13 MT-2	1 - 13	1/32" - 1/2"	MT-2	-	54	85	94	-	1,32
HX-13 MT-3	1 - 13	1/32" - 1/2"	MT-3	-	54	85	94	-	1,48
HX-13 MT-4	1 - 13	1/32" - 1/2"	MT-4	-	54	85	94	-	1,80
HX-16 MT-2	3 - 16	1/8" - 5/8"	MT-2	-	57	88	95	-	1,42
HX-16 MT-3	3 - 16	1/8" - 5/8"	MT-3	-	57	88	95	-	1,56
HX-16 MT-4	3 - 16	1/8" - 5/8"	MT-4	-	57	88	95	-	1,88
HX-13 VDI-30	1 - 13	1/32" - 1/2"	30	-	54	90	99	-	1,74
HX-13 VDI-40	1 - 13	1/32" - 1/2"	40	-	54	92	101	-	2,30
HX-13 VDI-50	1 - 13	1/32" - 1/2"	50	-	54	96	105	-	3,32
HX-16 VDI-30	3 - 16	1/8" - 5/8"	30	-	57	93	100	-	1,82
HX-16 VDI-40	3 - 16	1/8" - 5/8"	40	-	57	95	102	-	2,38
HX-16 VDI-50	3 - 16	1/8" - 5/8"	50	-	57	99	106	-	3,40
HX-13 CA40	1 - 13	1/32" - 1/2"	40	-	54	107	116	5/8" - 11	2,18
HX-13 CA40/R	1 - 13	1/32" - 1/2"	40	B+AD	54	107	116	5/8" - 11	2,18
HX-13 CA50	1 - 13	1/32" - 1/2"	50	-	54	88	97	1" - 8	3,86
HX-13 CA50/R	1 - 13	1/32" - 1/2"	50	B+AD	54	94	103	1" - 8	3,86
HX-16 CA40	3 - 16	1/8" - 5/8"	40	-	57	110	117	5/8" - 11	2,30
HX-16 CA40/R	3 - 16	1/8" - 5/8"	40	B+AD	57	110	117	5/8" - 11	2,30
HX-16 CA50	3 - 16	1/8" - 5/8"	50	-	57	91	98	1" - 8	3,96
HX-16 CA50/R	3 - 16	1/8" - 5/8"	50	B+AD	57	97	104	1" - 8	3,96
HX-13 R-8	1 - 13	1/32" - 1/2"	R-8	-	54	85	94	-	1,58
HX-16 R-8	3 - 16	1/8" - 5/8"	R-8	-	57	88	95	-	1,66

MORSE



DIN-69880 VDI
A, AD



CAT-ANSI
A, AD



R-8

