

HEXA SLIM PREMIUM

Portabrocas de Súper Precisión con cono integrado y Llave Torx.
Con CUERPO REDUCIDO para una óptima accesibilidad.

REFERENCIA	CAPACIDAD	CONO	REFRIG.	DIMENSIONES			PESO	EXCENTR.	EQUILIBR.	LLAVE
número	mm	tipo	interior	Ø	L1	L2	kg.	mm. (max.)	g/rpm	tipo
HG0084011	0,3-8	SK40	AD	35	70	75	1,15	0,02	G2,5/25000	TX25
HG0134011	0,5-13	SK40	AD	43	76	84	1,27	0,02	G2,5/25000	TX25
HG0164011	1-16	SK40	AD	50	80	90	1,49	0,02	G2,5/25000	TX25
HG0165011	1-16	SK50	AD	50	80	90	3,36	0,02	G2,5/25000	TX25

HG0134021	0,5-13	BT40	AD	43	92	100	1,52	0,02	G2,5/25000	TX25
HG0164021	1-16	BT40	AD	50	95	104	1,72	0,02	G2,5/25000	TX25
HG0165021	1-16	BT50	AD	50	106	116	4,37	0,02	G2,5/25000	TX25

HGK080631	0,3-8	HSK63	A	35	93	98	1,27	0,02	G2,5/25000	TX25
HGK130631	0,5-13	HSK63	A	43	101	109	1,39	0,02	G2,5/25000	TX25
HGK160631	1-16	HSK63	A	50	104	114	1,56	0,02	G2,5/25000	TX25
HGK161001	1-16	HSK100	A	50	110	120	3,25	0,02	G2,5/25000	TX25

HV0134041	0,5-13	CAT40	AD	43	77	85	1,31	0,02	G2,5/25000	TX25
HV0164041	1-16	CAT40	AD	50	81	91	1,48	0,02	G2,5/25000	TX25

HG0163061	1-16	VDI30	index	50	89,5	100	1,62	-	-	TX25
HG0164061	1-16	VDI40	index	50	89,5	100	2,19	-	-	TX25

HG0162571	1-16	CIL25	central	50	82	92	1,15	0,02	G6,3/15000	TX25
HG0163271	1-16	CIL32	central	50	82	92	1,31	0,02	G6,3/15000	TX25

HGC160631	1-16	PSC63	central	50	93,1	103	1,58	0,02	G2,5/25000	TX25
-----------	------	-------	---------	----	------	-----	------	------	------------	------

DIN-69871-A AD



MAS 403-BT (JIS-6339A) AD



DIN-69893-A (HSK)



CAT-ANSI A, AD



DIN-69880 VDI A, AD



DIN-1835 B



PSC63, CAPTO

