

HEXA SLIM VALUE

Portabrocas de Súper Precisión con cono integrado y Llave Torx.
Con CUERPO REDUCIDO para una óptima accesibilidad.

REFERENCIA	CAPACIDAD	CONO	REFRIG.	DIMENSIONES			PESO	EXCENTR.	EQUILIBR.	LLAVE
número	mm	tipo	interior	Ø	L1	L2	kg.	mm. (max.)	g/rpm	tipo
HH0164011	1-16	SK40	AD	50	80	90	1,49	0,05	G6,3/15000	TX25
HH0165011	1-16	SK50	AD	50	80	90	3,36	0,05	G6,3/15000	TX25

HH0164021	1-16	BT40	AD	50	95	104	1,72	0,05	G6,3/15000	TX25
HH0165021	1-16	BT50	AD	50	106	116	4,37	0,05	G6,3/15000	TX25

HH0164031	1-16	DIN40	-	50	85	95,5	1,58	0,05	G6,3/15000	TX25
HH0165031	1-16	DIN50	-	50	85	95,5	3,43	0,05	G6,3/15000	TX25

HHK160631	1-16	HSK63	A	50	104	114	1,56	0,05	G6,3/15000	TX25
HHK161001	1-16	HSK100	A	50	110	120	3,25	0,05	G6,3/15000	TX25

DIN-69871-A, AD



MAS 403-BT (JIS-6339A) AD



DIN-2080



DIN-69893-A (HSK)

