

SPS-SOLID

Portabrocas de autoapriete de Súper Precisión
con espiga integrada (cono morse, cilíndrica ó R-8)

SPS-13 MT-3



SPS-13 + espiga CM-3

REFERENCIA	CAPACIDAD		FIJACIÓN	DIMENSIONES				PESO
número	mm	pulgadas	K	Ø	L1	L2	L3	gr
SPS-08 MT-2	0,3 - 8	1/64" - 5/16"	morse taper 2	38	65	72	-	800
SPS-10 MT-2	0,5 - 10	1/32" - 3/8"	morse taper 2	43	73	82	-	1.020
SPS-13 MT-2	1 - 13	1/32" - 1/2"	morse taper 2	48	80	92	-	1.200
SPS-13 MT-3	1 - 13	1/32" - 1/2"	morse taper 3	48	80	92	-	1.320
SPS-13 MT-4	1 - 13	1/32" - 1/2"	morse taper 4	48	80	92	-	1.580
SPS-16 MT-2	3 - 16	1/8" - 5/8"	morse taper 2	54	85	96	-	1.600
SPS-16 MT-3	3 - 16	1/8" - 5/8"	morse taper 3	54	85	96	-	1.720
SPS-16 MT-4	3 - 16	1/8" - 5/8"	morse taper 4	54	85	96	-	1.980
SPS-13 CIL-20	1 - 13	1/32" - 1/2"	cyland. 20	48	80	92	60	1.320
SPS-13 CIL-25	1 - 13	1/32" - 1/2"	cyland. 25	48	80	92	61	1.320
SPS-13 CIL-32	1 - 13	1/32" - 1/2"	cyland. 32	48	80	92	63	1.440
SPS-16 CIL-20	3 - 16	1/8" - 5/8"	cyland. 20	54	88	98	60	1.600
SPS-16 CIL-25	3 - 16	1/8" - 5/8"	cyland. 25	54	88	98	61	1.680
SPS-16 CIL-32	3 - 16	1/8" - 5/8"	cyland. 32	54	88	98	63	1.800
SPS-13 R-8	1 - 13	1/32" - 1/2"	R-8	48	82	90	-	1.580
SPS-16 R-8	3 - 16	1/8" - 5/8"	R-8	54	87	98	-	1.800

Cono Morse



Mango Cilíndrico



R-8

